Rugasol[®] MH

through

Version 1.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	: Rugasol [®] MH
Product code	: 000000608808
Type of product	: liquid

Manufacturer or supplier's details

Company	: Sika Australia Pty. Ltd.
	55 Elizabeth Street
	Wetherill Park, NSW 2164
Telephone	: +61 2 9725 11 45
Telefax	: +61 2 9725 33 30
Emergency telephone num-	: +61 1800 033 111
ber	

SECTION 2. HAZARDS IDENTIFICATION

Flammable liquids	:	Category 3	
Skin corrosion/irritation		: Category 2	
Serious eye damage/eye irritation	:	Category 2A	
Specific target organ toxicity - sing	le exposure	Category 3 (Respiratory system)	
Specific target organ toxicity - repe sure (Inhalation)	eated expo-	Category 2 (hearing organs)	
Aspiration hazard	:	Category 1	
Short-term (acute) aquatic hazard		Category 2	
GHS label elements Hazard pictograms :			
Signal word :	Danger		
Hazard statements :	H304 May be f H315 Causes H319 Causes H335 May cau H373 May cau	serious eye irritation. se respiratory irritation. se damage to organs (hearing organs) epeated exposure if inhaled.	

Precautionary statements : **Prevention:**

Rugasol[®] MH

ersion 1.0	SDS Number: 000000608808	Revision Date: 12.11.20
	P210 Keep away from heat/sparks/o	pen flames/hot surfaces.
	No smoking.	
	P233 Keep container tightly closed.	
	P240 Ground/bond container and red	ceivina equipment.
	P241 Use explosion-proof electrical/	
	ment.	
	P242 Use only non-sparking tools.	
	P243 Take precautionary measures	
	P260 Do not breathe dust/ fume/ gas	
	P264 Wash skin thoroughly after har	
	P271 Use only outdoors or in a well-	
	P273 Avoid release to the environme	
	P280 Wear protective gloves/ eye pr	otection/ face protection.
	Response:	
	P301 + P310 IF SWALLOWED: Imm	leolately call a POISON
	CENTER or doctor/ physician.	r hair): Romaya/Taka off
	P303 + P361 + P353 IF ON SKIN (or immediately all contaminated clothing	
	shower.	g. Rinse skin with water/
	P304 + P340 + P312 IF INHALED: R	Remove victim to fresh air
	and keep at rest in a position comfor	
	POISON CENTER or doctor/ physici	
	P305 + P351 + P338 IF IN EYES: Ri	
	for several minutes. Remove contact	
	easy to do. Continue rinsing.	· •
	P314 Get medical advice/ attention if	f you feel unwell.
	P331 Do NOT induce vomiting.	
	P332 + P313 If skin irritation occurs:	Get medical advice/ atten-
	tion.	
	P337 + P313 If eye irritation persists	: Get medical advice/ at-
	tention.	
	P362 Take off contaminated clothing	
	P370 + P378 In case of fire: Use dry	sand, dry chemical or
	alcohol-resistant foam for extinction.	
	Storage: D402 + D222 Store in a well ventilete	d place. Keep container
	P403 + P233 Store in a well-ventilate tightly closed.	eu place. Reep containei
	P403 + P235 Store in a well-ventilate	ad place. Keep cool
	P405 Store locked up.	
	Disposal:	
	P501 Dispose of contents/ container	to an approved waste
	disposal plant.	
Other hazards whi	ch do not result in classification	
None known.		

R

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
xylene	1330-20-7	>= 20 - < 30
ethylbenzene	100-41-4	< 10

Rugasol[®] MH

Version 1.0

SDS Number: 000000608808



SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	 Risk of serious damage to the lungs (by aspiration). irritant effects Aspiration may cause pulmonary oedema and pneumonitis. Cough Respiratory disorder Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician	: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: Water
Hazardous combustion prod- ucts	: No hazardous combustion products are known
Specific extinguishing meth- ods	: Use water spray to cool unopened containers.

Rugasol[®] MH



Version 1.0

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	emove all source	ective equipment. es of ignition. aprotected persons.
Environmental precautions		om entering drains. aminates rivers and lakes or drains inform ties.
Methods and materials for containment and cleaning up	rbent material, (culite) and place	and then collect with non-combustible ab- e.g. sand, earth, diatomaceous earth, ver- e in container for disposal according to local ons (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take pre- cautionary measures against electrostatic discharges.
Advice on safe handling :	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage :	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

Rugasol[®] MH



Version 1.0

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL
		TWA	80 ppm 350 mg/m3	AU OEL
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	AU OEL
		STEL	125 ppm 543 mg/m3	AU OEL

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: red
Odour	: aromatic
Odour Threshold	: No data available
рН	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: > 138 °C (> 280 °F)

Rugasol[®] MH



Version 1.0	SDS Number: 000000608808	Revision Date: 12.11.2018
Flash point	: 24 °C (75 °F) Method: closed cup	
Evaporation rate	: No data available	
Flammability	: No data available	
Upper explosion limit	: Upper flammability limit 13 %(V)	
Lower explosion limit	: Lower flammability limit 1 %(V)	
Vapour pressure	: < 4 hPa (< 3 mmHg)	
Relative vapour density	: No data available	
Density	: 1.05 g/cm3 (20 °C (68 °F) ())	
Solubility(ies) Water solubility	: No data available	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: > 250 °C (> 482 °F)	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: > 7 mm2/s (40 °C)	
Explosive properties	: No data available	
Molecular weight	: No data available	
VOC-EU (solvent)	: 565.68 g/l	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reac- tions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available

Rugasol® MH

Version 1.0



No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

xylene: Acute oral toxicity	: LD50 Oral (Rat): 3,523 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): 1,700 mg/kg
ethylbenzene: Acute oral toxicity	: LD50 Oral (Rat): 3,500 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): 5,510 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components: xylene:

Rugasol[®] MH

ion 1.0	SDS Number: 000000608808	Revision Date: 12.11.2018
Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbo Exposure time: 96 h	w trout)): 3.3 mg/l
Persistence and degradabilit	у	
Bioaccumulative potential No data available		
Mobility in soil No data available		
Other adverse effects		
Product: Additional ecological infor-	: There is no data available for this pro	oduct
mation		

R

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)		UN 1263 Paint 3 III Flammable Liquids 366 355
IMDG-Code UN number Proper shipping name	:	UN 1263 PAINT
Class Packing group	:	3 III

Rugasol® MH

Version 1.0

SDS Number: 000000608808



Labels:3EmS Code:F-E, S-EMarine pollutant:no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number	:	UN 1263
Proper shipping name	:	PAINT
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	•3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule Scheduling of Medicines and Poisons	number allocated
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	: Not applicable
Prohibition/Licensing Requirements	: There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Date format : dd.mm.yyyy

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.